

# Admiral Line of Cabin Work Boats

## Model Standard Specifications Model A-2285

Length Overall: 22 ft.  
Beam Overall: 8 ft. 5 in.  
Standard Fuel Capacity: Optional  
Maximum O/B Horsepower: 230

### Propulsion

- Outboard
- Gasoline

Single or twin outboard motors can be transom or bracket mounted.

### Standard Equipment

- All Aluminum
- Pilothouse can be enclosed or open back
- Available in 5086 and 5052 alloy plate
- Hydraulic steering
- Adjustable operator's seat
- Navigation lights
- 12 volt DC electrical system w/ 8 circuit switch panel
- 2000 GPH electric bilge pump w/ auto-manual control
- Mooring bits (4)
- 4 in. Heavy Duty Rubber Bumper
- Safety rail on cabin
- Bow tow eye
- 5 lb. Sacrificial anodes (2)
- Safety non-skid decks and wide diamond plate gunnels
- Custom Fuel tanks
- Lifting eyes
- Push Knees
- Outboard protection bar (motor guard)
- Horn
- Bench Seats with Storage

Any of the Admiral Line of Cabin Work Boats can be customized to meet any requirements. Boats can be manufactured in lengths from 20' to 54'. A number of different Admiral models are listed below. Click on model number to view additional specifications, features, and options:

---

<b>Model</b>	<b>Length Overall</b>	<b>Beam Overall</b>
<b>A-2085</b>	20 ft	7 ft. 0 in.
<b>A-2285</b>	22 ft.	8 ft. 5 in.
<b>A-2485</b>	24 ft.	8 ft. 5 in.
<b>A-2685</b>	26 ft.	8 ft. 5 in.
<b>A-2885</b>	28 ft.	8 ft. 5 in.
<b>A-3285</b>	32 ft.	8 ft. 5 in.

## **Model A-2285 Construction Details**

Bottom Plating: 1/4 in.

Side Plating: 3/16 in.

Deck Plating: 3/16 in.

Cockpit Plating: 3/16 in.

Transom Plating: 1/4 in.

## **Options**

- Navigation and communication equipment
- Lifting davits/A-frame boom
- Flood lights/Docking lights
- Diving platform
- Safety equipment
- Towing bitt or frame
- Emergency lights
- Generators
- Air Conditioning/Heating Strip
- Radar
- VHF Radio
- Depth Sounder
- Custom Transducer Launcher
- Bow load ramp (electric or manual)
- Self bailing deck
- Motor Gill Bracket
- Custom Handrails
- Bottom Anti-foulant Coating
- Many other options available